



Technical Data Sheet

CleanAct Primer

Product Numbers 2010-001 & 2010-005

Updated January 2, 2008

CleanAct Rinseable Primer is a water based rinseable primer used directly on rubber roof (EPDM) applications to prepare the rubber substrate for acceptance of the **PremiumCoat System**.

ADVANTAGES & BENEFITS

- Excellent Rinseable primer for preparing the rubber roof surface.
- Deep cleans the rubber by removing dirt, grit, talc and oxidation with very little effort.
- Low cost per square foot.
- Environmentally safe
- No special tools or equipment necessary

PRODUCT CHARACTERISTICS

<u>Appearance-</u>	Clear
<u>Color-</u>	Light Pink
<u>State-</u>	Liquid
<u>Odor Characteristic-</u>	Mild odor
<u>pH-</u>	13 -13.5
<u>Vapor Density-</u>	1.0 Water
<u>Melting Point-</u>	0 C/ 32 F
<u>Boiling Point-</u>	100 C/ 212 F
<u>Percent Volatility-</u>	87 - 89%
<u>Evaporation Rate-</u>	>1 water

Storage and Shelf-Life-

CleanAct Primer has a shelf-life of nine (9) months provided it is stored in tightly

closed containers and protected from sunlight and stored at temperatures between 32° F (0C) and 100° F (38C).

APPLICATION INSTRUCTIONS:

Surface Preparation:

Mechanically remove all loose, laitance, grease or other contamination by blowing or sweeping.

Application

CleanAct Rinseable Primer comes ready to use. Apply primer by pump-up garden sprayer at 5 psi. One coat is all that is needed.

Allow **CleanAct Rinseable Primer** to remain on the rubber surface for 10 minutes.

After 10 minutes, power-wash at 1200 psi. This is a dirty water flushing. Once the power-washing has been done, power-wash a second time. This is a clean water rinse.

It is very important to do both power-washings. Allow the cleaned EPDM surface to completely dry after the second Power-washing before applying the full PremiumCoat System

Coverage

Coverage may vary due to surface condition of substrate.

Average coverage is approximately 150-200 square feet per gallon.

SAFETY & HANDLING

For specific information regarding safe handling of this material please refer to the Material Safety Data Sheet (MSDS). CleanAct Primer can be used in a safe and environmentally friendly manner while providing the customer with a high performance EPDM primer.

For more information: *Contact your Hydro-Stop Technical Sales Representative or call 1-800-739-5566*

CLEAN UP

Thoroughly rinse application equipment with clean water.

ORDERING INFORMATION

CleanAct Primer can be purchased in one gallon or five gallon pails at any official distributor of Hydro-Stop. For a distributor in your area please call us at 1-800-739-5566.