



RHINO-TOP

Features & Benefits

- ◆ Non Slip Coating
- ◆ Ready to apply, no mixing in sand.
- ◆ Tint to any color
- ◆ Water based
- ◆ Apply with roller

Ordering Information

Available in textured and smooth.

Please see last page for available bases and product codes.





RHINO-TOP

Directions

- ◆ Surfaces must be clean and dry, remove any loose paint or coatings.
- ◆ Prime unsealed surfaces with one coat of Rhino-Prime.
- ◆ Apply with roller $\frac{3}{4}$ " to 1" nap.
- ◆ Apply in 2 coats in opposite directions.
- ◆ Do not apply below 50°F.
- ◆ Dry to touch in 30 minutes Recoat 1-2 hours @ 70°F
- ◆ Allow 24 hour cure prior to service.





RHINO-TOP

Frequently asked questions

◆ ***Can I apply it over other paints and coatings?***

Yes. All paints and coatings must cure a minimum of 30 days prior to Rhino-Top application.

◆ ***Can it be applied over wood and asphalt surfaces?***

Yes. Prime unsealed surfaces with Rhino-Prime.

◆ ***Can it be used on garage floors or drive ways?***

No. Rhino-Top is not designed to handle car or vehicle traffic.





RHINO-TOP

Frequently asked questions

◆ *Is it waterproof?*

No. Please contact your QCP rep for details on other waterproofing products available.

◆ *Can it be sealed or top coated?*

Yes, Acrysheen and Graffiti Shield can be used over Rhino-Top.

◆ *Can it be used on walls for texture?*

Yes, Rhino-Top works great for texturing walls and other surfaces.





RHINO-TOP





RHINO-TOP

Available Bases

Rhino-Top Textured is available in 2 tinting bases.

Tint Base for light to medium colors: RT-T-TX-01

RT-T-TX-05

Accent Base for dark colors: RT-T-A-01

RT-T-A-05

Rhino-Top Smooth White is available for lines and detail work.

RT-S-W-01

RT-S-W-05

