

PRODUCT NAME: ELASTUFF 120 (UNIFLEX 1500) PART A CLEAR
- ELASTUFF 120 THIXO PART A CLEAR
PRODUCT CODE: EL-120-A-CL - EL-120-TX-CL-A

Manufacturer's Name : Quest Construction Products
Address : 1465 Pipefitter Street
: North Charleston, SC 29405
: INITIAL(FIRST CALL)CHEMTREC(800)424-9300
INFORMATION PHONE : (800)739-5566
TOLL FREE : BACKUP(800)541-4383
DATE REVISED : MAY 2012

~~~ SECTION 1 ~~~~ MANUFACTURER IDENTIFICATION ~~~~  
 ~~~ SECTION 2 ~~~~ HAZARDOUS INGREDIENTS/SARA III INFORMATION ~~~~

| Reportable Components | CAS Number | MM HG @ Temp | Weight |
|--|--------------|--------------------|--------|
| MDI Polybutadiene Prepolymer
No OEL's Established. | Not Assigned | | 75 |
| ~
Phthalate acid ester
No OEL's established. | 68515-45-7 | <0.075 68F/20C | 15 |
| ~
* Modified Diphenylmethane diisocyanate | 25686-28-6 | <0.0001 77F/25C | 9 |
| Also contains:
4-4' Diphenylmethane diisocyanate (MDI) (CAS* 101-68-8) and
Diphenylmethane Diisocyanate(MDI) Mixed Isomers (26447-40-5)
Isocyanate Prepolymer (Proprietary)
The following OEL's are for CAS* 101-68-8: | | | |
| TREATED FUMED SILICA | 112945-52-5 | N/A N/A | 0-5 |
| Silicon Dioxide (Synthetic) CAS#67762-90-7,
No OEL's for this specific ingredient, OEL's for Silica CAS# 7631-86-9:
OSHA PEL: 6mg/m3, ACGIH TLV: 10mg/m3
ACGIH TLV TWA: 0.005ppm, OSHA PEL, ceiling: 0.02ppm. | | | |
| ~
* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
* Indicates carcinogenic chemical.
NOTE: If tinted may contain Carbon Black CAS*1333-86-4 AND/OR Crystalline Silica CAS*14808-60-7. If tinted DARK GRAY or BLACK consider these levels to be reportable. | | | |

This MSDS may be used for other container sizes of this product. When parts A & B are combined, the hazard warnings for both components are present.

~~~ SECTION 3 ~~~~ HAZARDS IDENTIFICATION ~~~~

**Potential Health Effects**

**Eyes:**

Eye exposure, will cause intense burning of the eyes, photophobia, blepharospasm, profuse lacrimation, lid edema, and superficial corneal ulceration with a resulting reversible blindness. Contact with isocyanates may result in conjunctival irritation and mild corneal opacity. Isocyanate is reported to induce chemical burns in rabbit eye studies. A similar degree of eye injury may develop after contact with human eyes.

**Skin:**

Skin absorption is believed to generally be too slow to produce signs of acute systemic poisoning. However, animal studies have shown that respiratory sensitization can be induced by skin contact with known respiratory sensitizers, including isocyanates. Isocyanates are a primary skin irritant--they react with skin protein

and moisture and can cause irritation. Symptoms can include: redness, swelling, rash, scaling or blistering. Isocyanates are also strong skin sensitizers. Experience indicates that direct skin contact is the route of exposure most likely to cause skin sensitization. Once sensitized, an individual may react even to airborne levels below the TLV with the following symptoms; itching and tingling of the earlobes and neck, rash, hives, swelling of the arms and legs or other symptoms common to allergic dermititus. These symptoms may be immediate or delayed several hours. Prolonged contact can cause reddening, swelling, rash, scaling or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material or even as a result of vapor-only exposure.

**Ingestion:**

Swallowing may result in local irritation. Vomiting may also result. Do not allow vomit to be breathed into the lungs, as chemical pneumonitis and pulmonary edema/hemorrhage is possible. The isocyanate in this product is classified as "practically non-toxic" by ingestion. In humans, irritation or chemical burns and corrosive action in the mouth, pharynx, esophagus, stomach & digestive tract can develop following ingestion. Symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea. Injury may be severe and cause death.

**Inhalation:**

Repeated or prolonged exposure to vapors or mists are irritating to the respiratory tract. Inhalation of vapors and mists of isocyanate at concentrations above recommended exposure limits can irritate the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the intended recommended exposure level with similar symptoms as well as an asthma attack. Exposure to higher levels may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in the lungs). These effects are usually reversible. Chemical or hypersensitive pneumonitis, with flu-like symptoms (e.g., fever, chills) has also been reported.

---

~~~ SECTION 4 ~~~~ FIRST AID MEASURES ~~~~

Eyes:

For eye exposure, irrigate the exposed eyes with copious amounts of tepid water for at least 15 minutes. If the victim is wearing contact lenses, they should be removed, provided such removal does not cause further damage to the eyes. Consult a physician or ophthalmologist immediately.

Skin:

Remove product and immediately flush affected area with water for at least 15 minutes. Cover the affected area with a sterile dressing or clean sheeting and consult a physician immediately, except for the most minor, superficial and localized burns. Do not apply greases or ointments. Control shock if present. Discard or launder contaminated clothing before reuse. Contaminated leatherwear should be discarded.

Ingestion:

Do not induce vomiting. Give 1 to 2 cups milk or water. If vomiting occurs, keep victim's head below the hips to prevent breathing vomit into the lungs. Consult a physician immediately.

Inhalation:

Move to fresh air; administer oxygen by a qualified individual or artificial respiration as needed. Consult a physician immediately. Asthmatic-type symptoms may develop and may be immediate or delayed several hours. Treatment is essentially symptomatic.

Note to Physician:

Eyes - Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation frequently. Workplace vapors could produce reversible corneal epithelial edema impairing vision.

Skin- this compound is a potent skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn.

Ingestion - Treat symptomatically. There is no specific antidote.

Inducing vomiting is contraindicated because of the irritating nature of the compound.

Inhalation- treatment is essentially symptomatic. An individual having a dermal or pulmonary sensitization reaction to this material should be removed from any exposure to Isocyanate. Throughout a symptomatic victim's treatment course, monitor the ECG, chest x-ray, pulse oximetry, peak airflows, arterial blood gases, serum electrolytes, and renal and hepatic function

~~~ SECTION 5 ~~~~ FIRE FIGHTING MEASURES ~~~~

**Flammable Properties**

**Flash Point:** 200C/392F

**Lower Flammable Limits:** N/A

**Upper Flammable Limit:** N/A

**Auto Ignition Temperature:** Not available

**Extinguishing Media:**

Carbon dioxide, dry chemical, or appropriate foam. If water is used, very large quantities are required. Reaction between water and hot isocyanate may be vigorous. Contain run-off water with temporary barriers.

**Special Fire Fighting Procedures:**

Isolate fire area and deny unnecessary entry. Move container from fire area if this is possible without hazard. Stay upwind. Keep out of low areas where gases (fumes) can accumulate.

Personnel engaged in fighting Isocyanate fires must be protected against nitrogen dioxide fumes as well as Isocyanate vapors.

Firefighters must wear self-contained breathing apparatus and turnout gear.

---

~~~ SECTION 6 ~~~~ ACCIDENTAL RELEASE MEASURES ~~~~

Small Spill:

Clean up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. Evacuate area of all non-essential personnel. Ventilate area as vapors are heavier than air.

Clear the area of unnecessary personnel. Insure a trained response team is in emergency protective equipment. Prevent further spillage and contain the spill using dikes made of sand, earth or spill pillows. Cover the spill area with a non-combustable absorbant material (e.g., absorbant clay, earth, sand) to absorb as much liquid as possible. Shovel the absorbant into open top containers. Do not fill to the top or cover the containers. Prepare a decontaminating solution as follows:

Option 1: consists of a solution 90% water, 8% concentrated ammonia solution and 2% liquid detergent.

Option 2: consists of a solution 90-95% water, 5-10% sodium carbonate and 0.2-0.5% liquid detergent.

Pour the liquid decontaminant liberally over the remaining spill area and spread with a broom or squeegee to insure contact. Let stand 10-15 minutes @25c(77f), longer at lower temperatures. Then wash down the area with plenty of water. In a well ventilated area, add enough liquid decontaminant solution to the containers with the absorbed spill material to obtain an approximate 10:1 ratio of decontaminate solution to spill material. Mix the liquid-absorbant slurry and let stand for 12-24 hours. Stir periodically, or the liquid-absorbant slurry may solidify. Leave the lids on loosely. After decontamination solution has been in contact with the spilled material for 24-48 hours, and the evolved carbon dioxide has vented away, tighten down the lids and dispose of the mixture in accordance with local, state and federal regulations. Test the area for residual isocyanate vapors before allowing workers to re-enter the area. When safe working conditions have been re-established, remove and decontaminate all equipment used.

Large Spill:

Use same procedure as small spill.

~~~ SECTION 7 ~~~~ HANDLING AND STORAGE ~~~~

**Handling & Storage:**

Handling: Vapors can be evolved when material is heated during processing operations. See SECTION 8, Exposure Controls/Personal Protection, for types of ventilation required. Wash after handling and shower at end of work period. Avoid eye contact. Avoid skin contact. Do not breathe vapor. Material is hygroscopic and may absorb atmospheric moisture. Use dry nitrogen to purge opened, partially filled containers before resealing.

~  
Storage conditions: Store in a cool, dry and well ventilated place. Isolate from incompatible materials. Store in a tightly closed container.

Avoid contact with water, or moist air.

**Other Precautions:**

Avoid prolonged or repeated breathing of vapor or spray mist. If used indoors, provide mechanical exhaust ventilation. Use only in a well ventilated area. Wash thoroughly with soap and water before eating or smoking. Keep out of the reach of children. Do not get in eyes, on skin or on clothing. Avoid prolonged or repeated breathing of vapor.

Unused product remaining in opened containers must be purged with dry

nitrogen before resealing to prevent CO2 pressure build-up due to moisture contamination. If moisture or water contamination is suspected, do not reseal. Open sealed drums slowly to release any pressure due to possible CO2 pressure build-up.

---

~~~ SECTION 8 ~~~~ EXPOSURE CONTROLS/PERSONAL PROTECTION ~~~~

Engineering Controls:

In outside spray, mixing and rolling applications situate workers upwind of operation & provide airflow in a downwind direction so as to carry fumes and residual spray away from workers.

Hazard control from vapor or spray mist is ideally performed by the use of engineering controls. Effective engineering controls should be used whenever possible to eliminate and/or reduce worker exposure to all respiratory hazards. General ventilation, local ventilation, or isolation may prove adequate to keep airborne concentrations of diisocyanate below the exposure limit. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental concentrations.

Respiratory Protection:

The hazards of both part A and part B will be exhibited when combined.

Good industrial hygiene practice dictates that when Isocyanate-based coatings are mixed/sprayed and applied, some Type of respiratory protection should be worn.

A properly fitted air-purifying (combination organic vapor and particulate) respirator, proven by test to be effective in isocyanate containing spray/vapors during coating operations, and used in accordance with the recommendations of the manufacturer, can be used when the following conditions are met:

- concentration of vapors is unknown.
 - or concentrations exceed those in section II.
 - or the airborne Isocyanate (polymeric, oligomeric) concentration exceeds 5mg/m³ Averaged Over 8 Hours) OR 10mg/m³ average over 15 Minutes
 - or operations are being performed in confined space.
 - and a NIOSH certified end of service life indicator or a change schedule based upon objective information or data is used to ensure that cartridges are replaced before the end of their service life. In addition, pre-filters should be changed whenever breathing resistance increases due to particulate buildup.
- if a NIOSH certified end of service life indicator or a change schedule based upon objective information or data cannot be met, then a supplied air respirator must be used.

Monitoring: Refer To Patty's Industrial Hygiene And Toxicology-Volume 1(3rd Edition) Chapter 17 Volume III (First Edition) Chapter 3, for guidance concerning appropriate air sampling strategy to determine airborne concentrations of Isocyanate.

Medical surveillance: Supervision of all employees who handle or come in contact with this product is recommended. This should include pre-employment and periodical medical examinations with respiratory function test (fev, fvc as a minimum). Persons with asthma-type conditions, chronic bronchitis, other chronic respiratory diseases or

recurrent skin eczema or sensitization should be excluded from working with Isocyanate. Once a person is diagnosed as sensitized to Isocyanate, no further exposure can be permitted

Additional protective measures safety showers and eyewash stations should be readily available to work area. Educate and train employees in safe use of product. Follow all MSDS and label instructions.

Skin Protection:

Chemical resistant gloves determined to be impervious under the conditions of use.
The use of Tyvek suits are recommended to prevent skin exposure.

Eye Protection:

Eye Protection: Safety glasses with side shields recommended.

~~~ SECTION 9 ~~~~ PHYSICAL AND CHEMICAL PROPERTIES ~~~~

**Boiling Range:** 150C@ 5mmHg - 235-278C  
**Melting Point:** N/A  
**Specific Gravity(H2O=1):** .9331  
**Vapor Density(Air=1):** Heavier than air  
**Vapor Pressure:** .00001 mmHG @77F/25C.  
**Evaporation Rate(N-Butyl Acetate=1) :** Unknown  
**Coating V.O.C.:** 0.0 lb/gl                      **Coating V.O.C.:** 0 g/l  
**Material V.O.C.:** 0.0 lb/gl                      **Material V.O.C.:** 0 g/l  
**Solubility in Water:** Reacts slowly to liberate CO2, slightly soluble

**Appearance:** CLEAR LIQUID.

**Odor:** Aromatic odor.

**pH:** N/A

~~~ SECTION 10 ~~~~ STABILITY & REACTIVITY DATA ~~~~

Stability:

This product is stable under normal storage conditions

Conditions To Avoid:

Avoid extreme heat conditions and water contact. Reaction with water can result in pressure buildup of the container resulting in rupture of the container.
Avoid heat, open flames, welding arcs or other ignition sources which induce thermal decomposition and/or combustion.

Incompatible Materials:

Avoid contamination with oxidizing materials and/or water.

Hazardous Decomposition Products

Products of combustion include isocyanate vapor & mist, carbon monoxide, carbon dioxide, hydrogen cyanide, nitrogen oxides and sulfur oxides and unidentified products in fumes and smoke.

Hazardous Polymerization:

Not expected to occur

~~~ SECTION 11 ~~~~ TOXICOLOGICAL INFORMATION ~~~~

\*Data is for individual components of preparation.

**Materials having a known chronic/acute effects on eyes:**

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

**Materials having a known dermal toxicity.**

Dermal LD50: greater than 6,200mg/kg (rabbit)

**Materials having a known oral toxicity.**

For MDI, Oral LC50: >10,000mg/kg (rat)

**Materials having a known Inhalation hazard:**

Diphenylmethane diisocyanate (MDI), CAS 101-68-8 The 4-hour LC50 for polymeric MDI in rats ranges from 370 to 490 mg/m<sup>3</sup>. The 4-hour LC50 for monomeric MDI in rats was estimated 172-187mg/m<sup>3</sup>. The 1-hour LC50 for monomeric MDI aerosol was >2240mg/m<sup>3</sup> (rat).

**Identified Acute? Short-term Effects:**

Eye contact may result in conjunctival irritation and mild corneal opacity. Skin contact may result in dermatitis, either irritative or allergic.

Inhalation of MDI vapors may cause irritation of the mucous membranes of the nose, throat or trachea, breathlessness, chest discomfort, difficult breathing and reduced pulmonary function. Airborne overexposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema. Isocyanates have also been reported to cause hypersensitivity pneumonitis, which is characterized by flu-like symptoms, the onset of which may be delayed. Gastrointestinal symptoms include nausea, vomiting and abdominal pain.

**Identified Carcinogens? Longterm Effects:**

Results from a lifetime inhalation study in rats indicate that MDI aerosol was carcinogenic at 6mg/m<sup>3</sup>, the highest dose tested. This is well above the recommended TLV of 5ppb (0.05 mg/m<sup>3</sup>). Only irritation was noted at the lower concentration of 0.2 and 1 mg/m<sup>3</sup>. As a result of previous repeated over exposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the PEL/TLV. These symptoms, which include chest tightness, wheezing, cough, shortness of breath, or asthmatic attack, could be immediate or delayed up to several hours after exposure. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Chronic overexposure to isocyanates has also been reported to cause lung damage, including a decrease in lung function, which may be permanent. Sensitization may be either temporary or permanent. Prolonged contact can cause reddening, swelling, rash, scaling, or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material, or even as a result of vapor-only exposure.

**Identified Teratogens:**

NOT TERATOGENIC

**Identified Reproductive toxins :**

NO DATA.

**Identified Mutagens:**

For MDI mutagenicity studies concluded: Negative (mouse lymphoma specific locus mutation test with or without metabolic



activation) as well as positive (Salmonella microsomes test with metabolic activation; cell transformation assay) results have been observed "in vitro." The use of certain solvents which rapidly hydrolyze MDI is suspected of producing mutagenicity in some of these studies. MDI was negative in an "in vivo" (mouse micronucleus) assay.

--- SECTION 12 ~~~~ ECOLOGICAL INFORMATION ~~~~

**Ecotoxicological effects on plants and animals:**

MDI CAS\* 101-68-8: LC50 - 24hr (static): Greater than 500mg/Liter for Daphnia magna, Limnea stagnalis, and Zebra fish (Brachydanio rerio) for both polymeric and monomeric MDI.

**Chemical Fate :**

Immiscible with water, but will react with water to produce inert and non-biodegradable solids.

--- SECTION 13 ~~~~ DISPOSAL CONSIDERATIONS ~~~~

**Instructions:**

Dispose of contaminated product and materials used in cleaning-up, spills or leaks in a manner approved for this material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures. Empty containers will retain product residue and vapors and are subject to proper waste disposal, as above.

MDI: Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Empty decontaminated containers should be crushed to prevent reuse. DO NOT HEAT OR CUT EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH. Gases may be highly toxic and flammable.

--- SECTION 14 ~~~~ TRANSPORT INFORMATION ~~~~

**Shipping Information:**

DOT INFORMATION - 49 CFR 172.101

DOT DESCRIPTION - OTHER REGULATED SUBSTANCES, LIQUID, N.O.S., (CONTAINS 4,4'-DIPHENYLMETHANE DIISOCYANATE (MDI)), 9, UN 3082, PG III.

DOT REGULATED REPORTABLE QUANTITY: 6250 Lbs.

IMDG/IATA: DESCRIPTION: NON-REGULATED.

--- SECTION 15 ~~~~ REGULATORY INFORMATION ~~~~

**(Not meant to be all inclusive-selected regulations represented)**

**US Regulations:**

**Status Of Substances Lists:**

The concentrations shown in Section II are maximum ceiling levels (Weight %) to be used for calculations for regulations.

A reportable quantity is a quantity of a hazardous substance that triggers reporting requirements under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA).

If a spill of a substance exceeds its reportable quantity (RQ) in CFR 302.3, Table 40 302.4 Appendix A & 302.4 Appendix B, the release must be reported to The National Response Center At (800) 424-8802, The State Emergency Response Commission (SERC), and community emergency coordinators likely to be affected.

**Components present that could require reporting under the statute are:**

SEE SECTION II FOR PERCENTAGES

- \*TOXIC: NOT REPORTABLE IN QUANTITIES LESS THAN 1%
- \*CARCINOGEN: NOT REPORTABLE IN QUANTITIES LESS THAN .1%
- DIPHENYLMETHANE-4,4-DIISOCYANATE CAS \*101-68-8 RQ 5000\*.

Superfund Amendments And Reauthorization Act Of 1986 (SARA) Title III Requires emergency planning based on the Threshold Quantities(TPQ'S)and release reporting based on Reportable Quantities (RQ'S) In 40 CFR 355 Appendix A&B Extremely Hazardous Substances. The emergency planning and release requirements of 40 CFR 355 apply to any facility at which there is present any amount of any extremely hazardous substance(EHS) equal to or in excess of it's Threshold Planning Quantity(TPQ).

**Components present that could require reporting under the statute are:**

COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL THAT COULD REQUIRE REPORTING UNDER THE STATUTE ARE:

- DIPHENYLMETHANE-4,4-DIISOCYANATE CAS \*101-68-8 RQ 5000\*.
- 1,3-BUTADIENE CAS \*106-99-0 RQ 10\*.

EPCRA 40 CFR 372(Section 313) Requires EPA and the States to annually collect data on releases of certain toxic materials from industrial facilities, and make the data available to the public in the Toxics Release Inventory(TRI). This information must be included in all MSDS'S that are copied and distributed or compiled for this material. Reporting Threshold: Standard: A facility must report if it manufactures (including imports) or processes 25,000 pounds or more or otherwise uses 10,000 pounds or more of a listed toxic chemical during the calendar year.

**Components present that could require reporting under the statute are:**

**See Section II**

The components of this product are listed or excluded from listing on the US Toxic Substance Control Act (TSCA) chemical substance inventory. Mixtures shall be assumed to present the same health hazards as do the components which comprise one percent (by weight or volume) or greater of the mixture, except that the mixture shall be assumed to present a carcinogenic hazard if it has a component in concentrations of 0.1 percent or greater. The remaining percentage of unspecified ingredients, if any, are not contained in above DeMinimis concentrations and/or are believed to be non-hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200), and may consist of pigments, fillers, defoamers, wetting agents, resins, dryers, anti-bacterial agents, water and/or solvents in varying concentrations.

**International Regulations:**

**Canadian WHMIS:**

Methylene bisphenyl isocyanate CAS\*101-68-8

WHMIS Classification:

- D1A - Poisonous and infectious material - Immediate and serious effects - Very toxic
  - D2A - Poisonous and infectious material - Other effects - Very toxic
  - D2B - Poisonous and infectious material - Other effects - Toxic
- WHMIS Health Effects Criteria Met by this Chemical:
- D1A - Acute lethality - very toxic - immediate

D2B - Skin irritation - toxic - other  
D1B - TDG class 6.1 packing group III - toxic - immediate  
D2A - Respiratory tract sensitization - very toxic - other  
D2B - Skin sensitization - toxic - other  
WHMIS Ingredient Disclosure List:  
Included for disclosure at 0.1% or greater

**Canadian Environmental Protection Act (CEPA):**

All of the components of this product are exempt or listed on the DSL. See section 2 for composition/information on ingredients.

**EINECS:**

DIPHENYLMETHANE DIISOCYANATE HOMOPOLYMER  
CAS\*101-68-8                      EINECS\*:202-966-0

**State Regulations:**

**California:**

California Proposition 65: The following Statement is made in order to comply with The California Safe Drinking Water and Toxic Enforcement Act of 1986

"WARNING:This product contains the chemical(s) appearing below known to the State of California to:

**A: Cause Cancer**

NONE KNOWN

\*If tinted contains Carbon Black: CAS\*1333-86-4 and may also contain trace amounts of Crystalline Silica: CAS\*14808-60-7

**B: Cause Birth Defects or other Reproductive Harm :**

NONE KNOWN

In addition to the above named chemical(s)(if any), this product may contain trace amounts of chemicals, known to the State of California, to cause Cancer or Birth Defects and other Reproductive Harm

**Delaware:**

Listed on the Delaware Air Quality Management List:

METHYLENEBIS(PHENYLISOCYANATE) CAS\*101-68-8                      DRQ 5000\*  
RQ State: Federal Regulations Apply

**Florida:**

DIPHYLMETHANE DIISOCYANATE HOMOPOLYMER                      CAS\* 101-68-8  
LISTED AS TOXIC

**Idaho:**

Methylene Diphenyl Diisocyanate                      CAS\*101-68-8

Idaho Air Pollutant List:

Title 585--AAC: --                      Title 586--AAAC: --  
Title 585--EL: --                      Title 586--EL: --  
Title 585--OEL: --                      Title 586--OEF: --

**Massachusetts:**

DIPHYLMETHANE DIISOCYANATE HOMOPOLYMER                      CAS\*101-68-8  
SUBSTANCE CODES:2,4,F8,F9

**Michigan:**

NONE KNOWN

**Minnesota:**

DIPHYLMETHANE DIISOCYANATE HOMOPOLYMER                      CAS\*101-68-8  
LISTED IN THE MINNESOTA HAZARDOUS SUBSTANCES LIST:  
CODES:                      ANO

RATINGS: 12.36  
Status: Air Pollutant

**New Jersey:**

NEW JERSEY RTK HAZARDOUS SUBSTANCE  
Methylenebis(phenylisocyanate)4 CAS\* 101-68-8

**New York:**

DIPHLYMETHANE DIISOCYANATE HOMOPOLYMER CAS\*101-68-8  
New York List of Hazardous Substances:  
RQ--AIR: 1  
RQ--LAND: 1

**Pennsylvania:**

DIPHLYMETHANE DIISOCYANATE HOMOPOLYMER CAS\*101-68-8  
CODE:E

**Washington:**

DIPHLYMETHANE DIISOCYANATE HOMOPOLYMER CAS\*101-68-8  
WASHINGTON AIR CONTAMINANT: ppm mg/Cubic Meter  
TWA UNK 5  
STEL UNK UNK  
CEILING .02 .2  
SKIN:UNK

**Wisconsin:**

**West Virginia**

The following is on the West Virginia Toxic Air Pollutant  
List:  
Methylene Diphenyl Diisocyanate CAS\*101-68-8 (Pounds per Year):

~~~ SECTION 16 ~~~~ OTHER INFORMATION ~~~~

HMIS® III

Health : 3
Flammability : 1
Physical Hazard : 1

*Following Health rating Indicates Chronic/Carcinogenic Effects

HMIS® III Personal Protection : K

This rating is for the product as it is packaged. This rating will need
to be adjusted by the user based on conditions of use.

The information contained herein is furnished without
warranty of any kind. Users should consider these data only as a
supplement to other information gathered by them & determine the
suitability & completeness of information from all sources to assure
proper use & disposal of these materials & the safety & health of
employees & customers